



URSA WHITE BLOWING WOOL



PURE FLOC KD

Minerale inblaaswol



Spouwmuren

- ✓ Snelle en flexibele verwerking
- ✓ Thermisch, akoestisch en brandwerend
- ✓ Waterafstotend
- ✓ Materiaalbesparend, geen afval

R-WAARDE EN VERPAKKING

Isolatiedikte mm	Thermische weerstand R_0 $m^2 K/W$	Minimaal verbruik aantal zakken per 100m ²
40	1,2	7,2
50	1,5	9,0
60	1,8	10,8
70	2,1	12,7
80	2,4	14,5
90	2,6	16,3
100	2,9	18,1
120	3,5	21,7
140	4,1	25,3
160	4,7	28,9
180	5,3	32,5
200	5,9	36,1

TECHNISCHE INFO

Verplichte productkenmerken <ul style="list-style-type: none"> · Brandklasse (EUROKLASSE) · Densiteirange · Warmtegeleidingscoëfficiënt (λ_0) · Inzakking 	A1 30-65 kg/m³ 0,034 W/(m.K) Geen inzakking, S1
Specifieke productkenmerken <ul style="list-style-type: none"> · Luchtstromingsweerstand · Waterdampdoorlatendheid · Wateropname 	≥ 20 (AF₂₀) kPa.s/m² MU1 WS ≤ 1.0 (28d) kg/m²
Andere kenmerken <ul style="list-style-type: none"> · Gewicht per pak 	16,6 kg

TECHNISCHE INFO

Zakken/ pallet	Pallets/ truck	Gewicht (pallet) kg	Afmetingen (pallet) cm
39	16	647,40	165 x 110 x 285