



## PURE FLOC

Minerale inblaaswol



Houtskeletbouw  
& hellende daken

- ✓ Snelle en flexibele verwerking
- ✓ Thermisch, akoestisch en brandwerend
- ✓ Waterafstotend
- ✓ Materiaalbesparend, geen afval

### R-WAARDE EN VERPAKKING

Isolatie dikte mm	Thermische weerstand $R_0$ m <sup>2</sup> K/W	Minimaal verbruik aantal zakken per 100m <sup>2</sup>
60	1,8	10,8
80	2,4	14,5
100	2,9	18,1
120	3,5	21,7
140	4,1	25,3
160	4,7	28,9
180	5,3	32,5
200	5,9	36,1
220	6,5	39,8
240	7,1	43,4
260	7,6	47,0
280	8,2	50,6
300	8,8	54,2
320	9,4	57,8
340	10,0	61,4
360	10,6	65,1
380	11,2	68,7
400	11,8	72,3

### TECHNISCHE INFO

<b>Verplichte productkenmerken</b> <ul style="list-style-type: none"> <li>· Brandklasse (EUROKLASSE)</li> <li>· Densiteit</li> <li>· Warmtegeleidingscoëfficiënt (<math>\lambda_D</math>)</li> <li>· Inzakking</li> </ul>	<b>A1</b> <b>35 kg/m<sup>3</sup></b> <b>0,034 W/(m.K)</b> <b>Geen inzakking, S1</b>
<b>Specifieke productkenmerken</b> <ul style="list-style-type: none"> <li>· Doorstromingsweerstand</li> <li>· Waterdampdoorlatendheid</li> </ul>	<b>≥ 20 (AF<sub>20</sub>) kPa.s/m<sup>2</sup></b> <b>MU1</b>
<b>Andere kenmerken</b> <ul style="list-style-type: none"> <li>· Gewicht per pak</li> </ul>	<b>16,6 kg</b>

### TECHNISCHE INFO

Zakken/pallet	Pallets/truck	Gewicht (pallet) kg	Afmetingen (pallet) cm
39	16	647,40	165 x 110 x 285

